

# u[sonic]WS6 WEATHER SENSOR



The all new multi parameter sensor u[sonic]WS6 ...

The u[sonic]WS is the newest, most compact and system-capable addition to the Lambrecht meteo weather sensor series.

The sensor has no moving measuring elements and is therefore low-maintenance. The intelligent heating system works in relation to the wind speed and direction and keeps the sensor ice-free even under extreme weather conditions.

The u[sonic]WS6 easily meets the special challenges of alpine and maritime applications.

A wide variety of interfaces and protocols are available. There are no limits for the u[sonic]WS6 when it comes to its applications.

- without moving measuring elements
- 6 weather parameters: wind direction and speed, air temperature, rel. humidity, barometric pressure, dew point
- intelligent heating depending on wind speed and wind direction
- lamella shelter for accurate measurements of the temperature-humidity sensor
- easy installation, easy to maintain

## APPLICATIONS

- professional meteorological application
- wind turbines on- and off-shore
- ship weather station
- building automation and environmental engineering
- traffic and industrial meteorology
- wind warning and event engineering
- photovoltaic large-scale plants
- alpine applications

Professional Line	u[sonic]WS6 Weather sensor
Id-No.	00.16480.000000
Meas. range wind direction	0...359.9°
Meas. range wind speed	0...65 m/s
Meas. range air temperature	-40...+70 °C
Meas. range rel. humidity	0...100 %
Meas. range barometric pressure	300...1100 mbar
Accuracy wind direction	< 2° (> 1 m/s) RMSE
Accuracy wind speed	± 0,2 m/s RMSE (v < 10 m/s) • ± 2 % RMSE (10 m/s < v < 65 m/s)
Accuracy air temperature	± 0.1K (0...60 °C) • ± 0.2K (-40...0 °C)
Accuracy rel. humidity	typ. ± 1.5 % (0...80 %) r.h. • ± 2 % (80...100 %) r.h.

Continued on page 2

Professional Line	u[sonic]WS6 Weather sensor
Accuracy barometric pressure	± 0.5 mbar
Resolution wind direction	0.1°
Resolution wind speed	0.1 m/s
Resolution air temperature	0.1 °C
Resolution rel. humidity	0.1 %
Resolution barometric pressure	0.1 mbar
Trigger threshold	0.1 m/s
Protocols	NMEA 0183 • Modbus • SDI-12 (optional) • other protocols on request
Interface	RS485 / 422 • SDI-12 (optional)
Measuring rate	0.1...10 Hz
Operating conditions	-40...+70 °C (with heating: -50...+70 °C) • 0...100 % r. h.
Supply voltage	without heating: 6...60 VDC • with heating: 24 V AC/DC ± 20 %
Current consumption	sensor: typ. 50 mA at 24 VDC • with heating: max. 10 A at 24 V AC/DC
Heating data	factory configurable: 60 W / 120 W / 240 W (standard)
Dimensions	Ø 199 mm • height 238 mm
Housing	seawater resistant aluminium
Protection class	IP 66 • IP 67
Weight	approx. 3.1 kg
Standards	Salt fog: EN 60945 • Low voltage guide line: 72/23 EWG
EMC standards / Electrical safety	DIN EN 60945 • DIN EN 61000-4-2, 3, 4, 6, 11
Accessories (order separately)	32.16470.060000 sensor cable, 15 m, 8-pol. M16-plug

As of: 19.02.2020