

## Wall mounted INTERACUMULATORS

Series




### ICRV Model


IDROGAS CELSIOR Interaccumulators are available in capacities from 80 to 150 l. It is a range for domestic use and vertical wall installation.

They combine a modern and functional design with high quality construction and finishing.

- Vitrified interior treatment. Armored electrical resistance.
- Maximum protection against corrosion: Equipped with magnesium anode.
- Three levels of protection: Safety valve, working and safety thermostat
- Pilot light and connecting cable with plug.
- Included in the delivery: Anti-dielectric sleeves, safety valve and sheath. Right-hand coil inlets to G 3/4" H and sanitary water to G 1/2" M
- No thermal bridge: Up to 16% less energy loss.



	C (mm)	B (mm)
ICVR 80L	295	182
ICVR 100L	445	182
ICVR 120L	445	182
ICVR 150L	445	182



		CELSIOR VERTICAL INTERACCUMULATORS ICVR			
		CC20021	CC20022	CC20023	CC20024
		IDROGAS CELSIOR ICVR 80L	IDROGAS CELSIOR ICVR 100L	IDROGAS CELSIOR ICVR 120L	IDROGAS CELSIOR ICVR 150L
Volume [L]		79	96	116	139
Diameter [mm]		440	440	440	440
Resistance [W]		1500	1500	2000	2000
Surface Coil [m <sup>2</sup> ]		0.45	0.7	0.7	0.7
Coil Volume [L]		2.1	3.2	3.2	3.2
Warm-up Time ΔT45°C (15-60°C) [h:min]		0 h 18 min	0 h 18 min	0h 22 min	0h 26 min
Insulation thickness [mm]		32	32	32	32
ErP class		C	C	C	C
Heat Losses [W]		53	64	76	88
<b>Dimensions</b>					
Height [m]		0.843	0.983	1.148	1.312
Width [m]		0.440	0.440	0.440	0.440
Depth [m]		0.468	0.468	0.468	0.468