

# UV-IPC2122SR3-F40W-D

2 MP WiFi IP Camera

Easy range

1/2.7" Progressive Scan CMOS

4.0 mm Lens

IR LEDs Range 30 m

WEB, CMS, Smartphone and NVR  
interface



Uniview

WiFi IP camera

Easy range

1/2.7" Progressive Scan CMOS

2 Megapixel (1920x1080)

4.0 mm Lens

0 Lux

IR Range 30 m

Compression Ultra265/H.265/H.264

RJ-45 10/100 BaseT

802.11 b/g/n WiFi IEEE

Weatherproof IP67

IR Cut

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

# Specifications

Brand	Uniview
Range	Easy
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	1080p (1 ~ 20 FPS)
Extra Stream rate	2 <sup>o</sup> :720 (1 ~ 20 FPS), 3 <sup>o</sup> :D1 (1 ~ 20 FPS)
Compression	Ultra265/H.265/H.264
Lens	4 mm
Minimum illumination	0.02 Lux (Colour)
Infrared range	30 m
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Intelligent functions	Intrusion detection, human body detection, motion detection, sabotage detection
Internal memory	MicroSD card, Max 256 GB
Alarms	No
Audio	No
Network interface	Wi-Fi IEEE802.11b/g/n, Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 12V / 6W
Temp. operation	-35° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	157.3 (H) x 62.4 (W) x 56.6 (D) mm
Weight	450 g