

DHI-SSD-E900

NVMe M.2 Solid State Drive



- · Adopts high-quality 3D NAND wafer level chip
- Supports PCle3.0 x4, and NVMe 1.3 protocol
- All-metal cooling plate is included; equipped with intelligent temperature control technology
- · Supports TRIM to improve read/write performance and speed
- Supports Max. Write technology for full-disk SLC cache
- Supports LDPC ECC
- · Low power consumption management

System Overview

Equipped with high-quality 3D NAND wafer chip, high-performance controller and mature firmware solution, and worked with professional all-metal cooling plate, Dahua E900 series NVMe SSD provides efficient, stable and durable NVMe SSD.

*System configuration for performance test: Chip-Intel Z390 Chipset, Intel Core i9-9900KF@3.6GHz, 16GB DDR4; operating system-Windows 10 x64; testing tool-CrystalDiskMark 6.0.0

Scene

Dahua E900 series NVMe M.2 business-grade SSD can be used for enterprise and personal notebooks*, desktops, and other devices. Suitable for high workload environments such as making or editing videos or image rendering, it is designed for tech-savvy high-end user, gamers and professionals.

*All-metal cooling plate is included with E900 series. Please make sure that your device has enough space before installing.


Technical Specification				
Product Model	DHI-SSD-E900N256G	DHI-SSD-E900N512G	DHI-SSD-E900N1TB	
Capacity ¹	256 GB	512 GB	1 TB	
Form Factor	M.2 2280			
Port	PCle Gen 3.0 x 4			
Net Weight	Max 8 g (0.02 lb)			
Product Dimensions ²	80.0 mm × 23.0 mm × 4.8 mm (3.15" × 0.91" × 0.19")			
Packaging Dimensions	140.5 mm × 105.5 mm × 15.5 mm (5.53" × 4.15" × 0.61")			
Memory Component	3D TLC			

Power Consumption ²	2597 mW (max) 528 mW (idle)	2848 mW (max) 528 mW (idle)	3696 mW (max) 528 mW (idle)
S.M.A.R.T	Support		
TRIM	Support		
Garbage Collection	Support		
Sequential Read ²	Up to 2000 MB/s	Up to 2000 MB/s	Up to 2000 MB/s
Sequential Write ²	Up to 1250 MB/s	Up to 1550 MB/s	Up to 1800 MB/s
4K Random Read ²	Up to 97000	Up to 160000	Up to 230000
4K Random Write ²	Up to 190000	Up to 200000	Up to 230000
MTBF	1,500,000 hours		
Operating Temperature	0°C to 70°C (32°F to 158°F)		
Storage Temperature	-40°C to 85°C (-40°F to 185°F)		
Operating Humidity	5%–95% (non-condensing)		
Vibration Resistance	7–800 Hz, 3.08 G		
Shock Resistance	1500 G/0.5 ms (half sine wave)		
TBW	128 TB	256 TB	512 TB
Warranty ³	3-year limited warranty		
Reference Information	1. Capacity calculation: 1 GB = 1 billion bytes (IDEMA). Actual available capacity might be reduced (due to formatting, partition, operating system applications, or other necessary usage). 2. The dimensions are after installing cooling plate. 3. System configuration of performance test: Intel Z390 Chipset, Intel Core i9-9900KF@3.6GHz, 16GB DDR4,; operating system-Windows 10 x64; testing tool-CrystalDiskMark 6.0.0. 4. Warranty period or maximum write amount (TBW), whichever comes first. 5. High performance SLC cache has been enabled.		

E900 Series | DHI-SSD-E900

Ordering Information				
Туре	Model	Description		
E900 Series	DHI-SSD-E900N256G	M.2 2280 PCIe G3x4 (Dramless) SSD DHI-SSD-E900N256G		
	DHI-SSD-E900N512G	M.2 2280 PCle G3x4 (Dramless) SSD DHI-SSD-E900N512G		
	DHI-SSD-E900N1TB	M.2 2280 PCIe G3x4 (Dramless) SSD DHI-SSD-E900N1TB		

Installation



Dimensions (mm[inch])

