

## NYS230

1/4" open jack, stereo 3 pole, with washer and nut, with 0.205" faston tabs



### Article Variations

Article Name	Details	Packaging
NYS230	for up to 3.5 mm panel thickness	

## Technical Information

### Product

<b>Title</b>	NYS230
<b>Connection Type</b>	Jack

### Electrical

<b>Contact Resistance</b>	≤10 mΩ
<b>Insulation Resistance</b>	>2000MΩ(Initial)
<b>Dielectric Strength</b>	500V dc 50HZ

### Mechanical

<b>Insertion and Withdrawal Force</b>	5-40N
<b>Lifetime</b>	>5000 Mating Cycles

### Material

<b>Tube</b>	Brass
<b>Nut</b>	Brass
<b>Washer</b>	Steel
<b>Washer</b>	Steel
<b>Washer</b>	3240 Epoxy-phenolic
<b>Insulator Washer</b>	3240 Epoxy-phenolic
<b>Contact</b>	Bronze
<b>Sleeve Contact</b>	Brass
<b>Contact</b>	Bronze
<b>Tube</b>	Nickel Plating
<b>Nut</b>	Nickel Plating
<b>Washer</b>	Nickel Plating
<b>Washer</b>	Nickel Plating
<b>Contact</b>	Tin and Cer
<b>Sleeve Contact</b>	Tin and Cer
<b>Contact</b>	Tin and Cer