


Type	V <sub>R</sub> max (V)	I <sub>O</sub> I <sub>F</sub> <sup>*</sup> max (mA)	V <sub>F</sub> / I <sub>F</sub> max (V) (mA)	I <sub>R</sub> / V <sub>R</sub> max (μA) (V)	I <sub>R</sub> / V <sub>R</sub> / T <sub>amb</sub> max (μA) (V) (°C)	Case
------	------------------------------	--	--	--	--	------

**tungsten point contact - general purpose**

**T<sub>amb</sub> = 25°C**

pointe tungstene - usage général


1N 34	50	30	1	5	30	10				 <p>DO 7 (CB-26)</p>
1N 48	70	50	1	4	830	50				
1N 54 A	50	30	1	5	7	10	100	50	25	
1N 63	100	50	1	4	50	50	25	10	25	
1N 65	70	50	1	2,5	200	50				
1N 81	40	40	1	3	10	10	100	40	25	
1N 126 A	60	30	1	5	800	50	50	10	25	
1N 127 A	100	30	1	3	300	50	25	10	25	
1N 128	40	30	1	3	10	10				
1N 198	80	30	1	4	50	50	250	50	75	
1N 933	80	30	1	4	80	80	250	50	75	
AA 117	90	30	3,3	30	280	100	250	75	60	
AA 118	90	30	2,6	30	250	100	250	75	60	
AA 131	25	30	1	1,7	220	25				
AA 132	100	30	1,8	10	120	60				
SFD 108	100	50*	1	5	7	10	380	100	55	

Type	V <sub>R</sub> max (V)	I <sub>O</sub> max (mA)	V <sub>F</sub> / I <sub>F</sub> max (V) (mA)	I <sub>R</sub> / V <sub>R</sub> max (μA) (V)	I <sub>R</sub> / V <sub>R</sub> / T <sub>amb</sub> max (μA) (V) (°C)	t <sub>rr</sub> / I <sub>F</sub> (ns) (mA)	Case
------	------------------------------	-------------------------------	--	--	--	---	------

**tungsten point contact - switching**

**T<sub>amb</sub> = 25°C**

pointe tungstene - commutation


26 P 1	50	50	1	5	50	50	25	10	25	500	30	 <p>DO 7 (CB-26)</p>
FS 36	30	30	2	30	10	10	250	30	25	300	10	
SFD 105	30	30	1	5	30	10	500	30	55	160	10	

Type	V <sub>R</sub> max (V)	I <sub>O</sub> max (mA)	V <sub>F</sub> / I <sub>F</sub> max (V) (mA)	I <sub>R</sub> / V <sub>R</sub> max (μA) (V)	I <sub>R</sub> / V <sub>R</sub> / T <sub>amb</sub> max (μA) (V) (°C)	Case
------	------------------------------	-------------------------------	--	--	--	------

**tungsten point contact - detection**

**T<sub>amb</sub> = 25°C**

pointe tungstene - détection

1N 541	30	35	1	4	18	10	500	45	60	 <p>DO 7 (CB-26)</p>
1N 542 (1)	30	35	1	4	18	10	500	45	60	
AA 143 S	25	60	0,52	15	100	25				
AA 113 (1)	60	10	1	3,5	120	30	500	60	25	
AA 119 (1)	30	35	1	4	18	10	500	45	60	
SFD 107	10	20	1	4,5	220	10				
AA 130										

(1) 2.AA 113 : matched pair of AA 113  
2.AA 113 : Deux AA 113 appareillées


2.AA 119 : matched pair of AA 119  
2.AA 119 : Deux AA 119 appareillées

1N 542 : Sold by matched pairs (2 × 1N 542)  
1N 542 : Livrées par paires appareillées (2 × 1N 542)

**tungsten point contact - video detection**

**T<sub>amb</sub> = 25°C**

pointe tungstene - détection vidéo

1N 60	25	30	0,5	0,375	200	10				 <p>DO 7 (CB-26)</p>
1N 64	15		1	3	25	10				
1N 87	23	30	0,25	0,1	10	1,5	650	20	60	
1N 295	40	35	0,5	0,375	200	10				
AA 112	20	20	1	6	150	20	250	20	55	
AA 116	20	20	0,25	0,1	150	20				
AA 121	25	30	1	7	12	2				
AA 123	18	30	1	4	1,5	1				
SFD 104	25	20	1	6	400	25	500	25	55	
AA 114										
SFD 106	25	30	1	5	10	1,5	200	25	25	
SFD 111	25	30	1	6	6	2	150	20	25	
SFD 112	40	20	1	2,7	12	5	220	25	25	