

Contemporary Spiral Staircase Type "Enna"

(with metal treads, R2C railing and synthetic brushed stainless steel handrail) $\,$



www.1001stairs.com

Contemporary Spiral Staircase Type "Enna"

- This patented design combines Italian sophistication with the practical benefits of stateof-the-art materials. The out-of-the-ordinary configuration is instantly recognisable and suits any modern interior.
- The Enna has a central helical structure that is made from modular inserts which enable the direction of ascent and height of the treads to be rotated.
- This custom made staircase is available in widths: 1100, 1200, 1300, 1400, 1500 and 1600mm.
- The standard staircase includes 11 treads + platform and stair railing with handrail.
- The Enna is available with metal <u>or</u> wooden treads and a diverse range of balustrades. Kick boards can also be fitted to the wooden tread configuration to create a sinuous yet harmonious streamlined look.
- The 40mm wooden treads are made from 1st choice beech hardwood with 10 standard finishes natural beech, light walnut, dark walnut, mahogany, cherry, wengé, bleached white, smokey grey, dove or oak.
- The metal landing platform and treads are made from pressed steel. They are powder coated and coloured either white, aluminium grey, dove grey or black.
- The Enna is easy to assemble and comes with a wide range of accessories that allow you customise the staircase to your own design.
- We recommend customers consult their building control office prior to installing any staircase to check that it fully meets their requirements.
- A complete easy to follow installation guide is provided.
- Please call or email for design and/or configuration assistance.



Email: info@1001stairs.com



 The stairwell must be at least 50mm larger than the diameter of the staircase ie. Ø1250, Ø1450 or Ø1650mm.

Rises and Treads

- The standard staircase fits a floor-to-floor total height of 2320-2760mm with 12 rises (11 treads + landing platform).
- The rise can be adjusted between 210-230mm.

Total Height	No. of Rises	No. of Treads	
2320-2760mm	12	11	Standard
2730-2990mm	13	12	+1 tread
2940-3220mm	14	13	+2 treads
3150-3450mm	15	14	+3 treads
3360-3680mm	16	15	+4 treads